

Application No 09/584 363  
Amendment dated May 9, 2005  
Reply to Office Action dated February 8, 2005

### **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of the claims in the application:

### **Listing of Claims:**

1. (cancelled)
2. (cancelled)
3. (currently amended) A photonic switch for a DWDM network comprising:  
a plurality I of input ports and a plurality I' of output ports;  
an optical demultiplexer for separating a wavelength  $\lambda_k$  from an input multichannel signal  $S_{in}(k,i)$  received on an input port i of said plurality of input ports, and for directing said wavelength  $\lambda_k$  on an assigned ingress area along a predetermined input path in such a manner that the predetermined input path does not require focusing means;  
a switching block for directing said wavelength  $\lambda_k$  along an optical path from said assigned ingress area to an associated egress area selected from a plurality of egress areas;  
an optical multiplexer for directing said wavelength  $\lambda_k$  from said associated egress area along a predetermined output path, and for combining said wavelength  $\lambda_k$  into an output multichannel signal  $S_{out}(k',i')$ , transmitted on an output port i' of said plurality of output ports;  
wherein said switching block comprises a switch fabric for cross-connecting said wavelength  $\lambda_k$  from said input multichannel signal  $S_{in}(k,i)$  to said output multichannel signal  $S_{out}(k',i')$  and a control unit for selecting said associated egress area and for configuring said switch fabric to direct said wavelength along an adaptable path between said assigned ingress area and said associated egress area and,  
wherein said switch fabric comprises an input matrix with K rows and I columns of input optical switching elements, and an output matrix with K' rows and I' columns of output optical switching elements; wherein each input port of said plurality of input

Application No. 09/584 363  
Amendment dated May 9, 2005  
Reply to Office Action dated February 8, 2005

ports is associated with a column of said input matrix and each wavelength arriving on said each input port is associated with a row of said input matrix, and wherein each output port of said plurality of output ports is associated with a column of said output matrix and each wavelength transmitted at each said output port is associated with a row of said output matrix and wherein said adaptable path transits said switch fabric such than an input optical switching element of said input matrix redirects said wavelength away from the a plane of said input matrix to an output optical switching element of said output matrix.

4. (currently amended) A photonic switch as claimed in claim 3, wherein said switching elements have a minimum of four degrees of freedom of orientation.
5. (original) A photonic switch as claimed in claim 3, wherein said switching elements are 3-D MEMS mirrors.
6. (currently amended) A photonic switch as claimed in claim 3, wherein said optical demultiplexer and said input ports are arranged in a predetermined position relative to each other along said predetermined input path, for separating each input multichannel signal into component wavelengths according to an area angle of incidence of said input multichannel signal on said demultiplexer.
7. (original) A photonic switch as claimed in claim 6, wherein said demultiplexer and said input matrix are arranged in a predetermined position relative to each other along said predetermined input path, for directing each said component wavelength from said demultiplexer to said input matrix according to said wavelength  $\lambda_k$  and said input port  $i$ .
8. (cancelled)
9. (currently amended) A photonic switch as claimed in claim 3, wherein said multiplexer and said output ports are arranged in a predetermined position relative to each other along said predetermined output path, for combining all wavelengths arriving in a certain area of incidence on said multiplexer within an output ~~multichannel signal~~ port.

Application No. 09/584 363  
Amendment dated May 9, 2005  
Reply to Office Action dated February 8, 2005

10. (currently amended) A photonic switch as claimed in claim 9, wherein said demultiplexer and said output matrix are arranged in a predetermined position relative to each other ~~along said predetermined output path~~, for directing each said wavelength  $\lambda_k$  from said output matrix to said certain area of incidence according to said wavelength  $\lambda_k$  and said input port  $i$ .
11. (currently amended) A photonic switch as claimed in claim 10, further comprising optical elements arranged along said ~~second~~ predetermined output path for directing said wavelength from said egress area on said ~~associated~~ output port.
12. (previously presented) A photonic switch as claimed in claim 3, wherein  $|=I'$  and  $i=i'$ .
13. (previously presented) A photonic switch as claimed in claim 3, wherein  $K=K'$ ,  $k=k'[[i]]$ ,  $I=I'$  and  $i=i'$ .
14. (previously presented) A photonic switch as claimed in claim 3, wherein said switch fabric further comprises an add zone for cross-connecting an add wavelength incident on said add zone to said output multichannel signal; and said control unit further capable of configuring said switch fabric to direct said add wavelength along an adaptable add path between said add zone and said associated egress area.
15. (original) A photonic switch as claimed in claim 14, further comprising a plurality of add ports.
16. (previously presented) A photonic switch as claimed in claim 15, wherein said input matrix further comprises an add zone of M rows and N columns of input optical switching elements, wherein each add port of said plurality of add ports is associated with a column of said add zone and each wavelength arriving on said each add port is associated with a row of said add zone.
17. (previously presented) A photonic switch as claimed in claim 3, further comprising at least one drop port,

Application No. 09/584,363  
Amendment dated May 9, 2005  
Reply to Office Action dated February 8, 2005

wherein said switch fabric further comprises a drop zone for cross-connecting a drop wavelength from said input multichannel signal on said drop zone; and  
a control unit for configuring said switch fabric to direct said drop wavelength along an adaptable drop path between said assigned ingress area and said drop zone.

18. (previously presented) A photonic switch as claimed in claim 17, further comprising a plurality of drop ports.
19. (previously presented) A photonic switch as claimed in claim 18, wherein said switch fabric further comprises a drop zone of M' rows and N' columns of output optical switching elements, wherein each drop port of said plurality of drop ports is associated with a column of said drop zone and each wavelength arriving on said each drop port is associated with a row of said drop zone.
20. (currently amended) A method of routing a wavelength within a photonic switch of DWDM network, comprising:  
pre-establishing an input optical path between an input port associated with said wavelength, through an assigned ingress area to an assigned optical switching element of an input matrix, according to a connectivity map in such a manner that a part of the input optical path comprised between the assigned ingress area and the assigned optical switching element does not require focussing means;  
establishing an adaptable path from said assigned optical switching element to an associated optical switching element of an output matrix wherein said adaptable path transits said switch fabric such that an input optical switching element of said input matrix redirects said wavelength away from the a plane of said input matrix to an output optical switching element of said output matrix; and  
pre-establishing an output optical path between said associated optical switching element through an associated egress area to an output port of interest according to said connectivity map.
21. (original) A method as claimed in claim 20, further comprising  
transiting said adaptable route to connect said assigned optical switching element to another optical switching element of said output matrix, whenever said connectivity map changes.

Application No. 09/584,363  
Amendment dated May 9, 2005  
Reply to Office Action dated February 8, 2005

22. (currently amended) A photonic switch for routing a plurality of wavelengths of a ~~DWD~~ DWDM transport network, between a plurality of input ports and a plurality of output ports comprising:

an all-optical switch fabric for cross-connecting a wavelength  $\lambda_k$  from an optical input multichannel signal  $S_{in}(k,i)$  to an optical output multichannel signal  $S_{out}(k',i')$ , along an adaptable optical path;

a control unit for configuring said adaptable optical path;

an optical demultiplexer for separating said wavelength  $\lambda_k$  from said optical input multichannel signal  $S_{in}(k,i)$  and directing said wavelength  $\lambda_k$  on an assigned ingress area of said all-optical switch fabric along a predetermined input path in such a manner that the predetermined input path does not require focusing means; and

an optical multiplexer for receiving said wavelength  $\lambda_k$  received along a predetermined output path from an associated egress area of said all-optical switch fabric, and combining said wavelength  $\lambda_k$  with said optical output multichannel signal  $S_{out}(k',i')$ ;

wherein said ~~all-optical~~ all-optical switch fabric comprises an input matrix of K rows and I columns of optical switching elements, and an output matrix with K' rows and I' columns of output optical switching elements,

wherein said adaptable path transits said ~~all-optical~~ all-optical switch fabric such that an input optical switching element of said input matrix redirects said wavelength away from ~~the~~ a plane of said input matrix to an output optical switching element of said output matrix;

wherein each input port of said plurality of input ports is associated with a column of said input matrix, and each wavelength of said plurality of wavelengths is associated with a row of said input matrix; and

wherein each output port of said plurality of output ports is associated with a column of said output matrix and each wavelength of said plurality of wavelengths is associated with a row of said output matrix.

23. (cancelled)

24. (cancelled)

Application No. 09/584 363  
Amendment dated May 9, 2005  
Reply to Office Action dated February 8, 2005

25. (cancelled)
26. (cancelled)
27. (previously presented) A photonic switch as claimed in claim 22, further comprising an add port, and wherein said ~~all-optical~~ all-optical switch fabric comprises an add zone of M rows and N columns of input optical switching elements, wherein said add port is associated with a column of said add zone and each wavelength arriving on said add port is associated with a row of said add zone.
28. (cancelled)
29. (previously presented) A photonic switch as claimed in claim 22, further comprising a drop port wherein said switch fabric comprises a drop zone of M' rows and N' columns of optical switching elements, wherein said drop port is associated with a column of said drop zone and each wavelength arriving on said drop port is associated with a row of said drop zone.
30. (original) A photonic switch as claimed in claim 3, wherein said input and said output matrices are arranged in two different planes.
31. (currently amended) A photonic switch as claimed in claim 30, wherein said planes are substantially parallel to each other.
32. (currently amended) A photonic switch as claimed in claim 3 wherein said input and output matrices are arranged substantially in the same plane and wherein said switch switching block further comprises directing means arranged in the path of the light between said input and output matrices.